

SHELVING

AMCO PLASTEEL® SHELVING



ITEM # _____ MODEL # _____ QTY: _____
 PROJECT: _____
 OPTIONS: YES _____ NO _____




Plasteel® Mobile Unit



Plasteel® Solid Shelf
PS1836S



Plasteel® Vented Shelf
PS1836V



Nylon Collet



Steel Reinforced Shelf

Standard Features & Benefits

- ◆ Steel-reinforced plastic shelves support 1,000 lbs. each
- ◆ Available solid or vented. Solid style has raised edge to contain liquid spills
- ◆ Constructed of high-impact structural foam plastic
- ◆ Flexible unit accommodates full line of Amco shelves
- ◆ Solid style accepted by the U.S. Department of Agriculture for direct food contact
- ◆ Stainless Steel posts won't rust, also available with Grey Bond™ or Polygard® posts

Finish	Suffix	Color
Polygard®	PG	Blue
Grey Bond™	GR	Grey
Stainless Steel	SS	

*Select a finish. Add suffix to model number.

For SPG's complete product menu, visit www.spgusa.com or call 877.503.4SPG (4774)



SHELVING

AMCO PLASTEEL® SHELVING

Specifications

SHELVES

Shelf frames are constructed of .0475" thick 1" O.D. steel square tubing. Frames of 60" long shelves have an additional tube welded longitudinally onto the center of the frame. A square tapered 1-3/4" high steel collar is welded at each corner of the frame. Shelves are constructed of high density polyethylene structural foam and steel parts are covered with hard baked grey plastic resin coating. Top perimeter includes a beveled marine edge.

POSTS

Posts are constructed of .065" thick square tubes with notches on every 2" of each corner. A nylon cap is installed on the top of the post. The leveler on the bottom of the post has a 7/8" hex head and a 3/4" threadless shoulder to eliminate deposits of mop strands and broom fibers.

ASSEMBLY

Each shelf comes with four nylon tapered collets that fit securely within any of the notches on the post. Posts are connected to the tapered shelf collars without the need for additional tools or hardware.

Shelving

Vented Model No.	Solid Model No.	W x L		Weight	
		(In.)	(mm.)	(Lbs.)	(Kg.)
PS1836V	PS1836S	18 ³ / ₄ x 36 ¹ / ₂	476 x 927	16	7.3
PS1842V	PS1842S	18 ³ / ₄ x 42 ¹ / ₂	476 x 1080	17	7.7
PS1848V	PS1848S	18 ³ / ₄ x 48 ¹ / ₂	476 x 1232	21	9.5
PS1860V	PS1860S	18 ³ / ₄ x 60 ¹ / ₂	476 x 1537	29	13.2
PS2436V	PS2436S	24 ³ / ₄ x 36 ¹ / ₂	629 x 927	19	8.6
PS2442V	PS2442S	24 ³ / ₄ x 42 ¹ / ₂	629 x 1080	21	9.5
PS2448V	PS2448S	24 ³ / ₄ x 48 ¹ / ₂	629 x 1232	25	11.3
PS2460V	PS2460S	24 ³ / ₄ x 60 ¹ / ₂	629 x 1537	33	15

Posts

Model No.*		Height		Weight	
Stationary	Mobile Posts	In	mm	Lbs	Kg
P08	PC08	8	200	1	0.5
P14	PC14	14	355	2	0.9
P34	PC34	34	865	3	1.4
P54	PC54	54	1370	4	1.8
P64	PC64	64	1625	4-1/2	2
P72	PC72	72	1830	5	2.3
P84	PC84	84	2130	5-1/2	2.5

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke

SPG International, LLC
11230 Harland Drive NE
Covington, GA 30014
877-503-4SPG (4774)

www.spgusa.com

The best names in the business
all have one thing in common.

EXPECT MORE
SPG
STORAGE PRODUCTS GROUP