

# SECURITY SHELVING



ITEM# _____	MODEL# _____	QTY: _____
PROJECT: _____		
OPTIONS: <input type="checkbox"/> YES _____ <input type="checkbox"/> NO _____		



SU1316CP – 24x48x72 4-Shelf Stationary Security Unit

## Standard Features & Benefits

- ◆ Lockable wire enclosure limits opportunities to steal, reducing losses due to theft.
- ◆ Provides a secure area with adjustable shelving for storage of costly food products, wine, liquor, linen, expensive serving pieces, valuable tools, and other items that tend to disappear.
- ◆ Enclosure designed with 2" x 2" wire spacing to prevent small goods from being removed.
- ◆ Door secures at both top and bottom, and handle has hasp design so it can be padlocked (padlock not included).
- ◆ Shelves and posts may be ordered in any available finish. Enclosure available in Plating Plus finish only.
- ◆ Available in stationary and mobile models. Choose from a variety of standard caster offerings



<b>Model:</b>
<input type="checkbox"/> SU _____
<input type="checkbox"/> SU _____ MO _____

For SPG's complete product menu, visit [www.spgusa.com](http://www.spgusa.com) or call 877.503.4SPG (4774)



# SECURITY SHELVING



## Specifications

### For Assembled Shelving Units

#### Diagram Reference

X. Spacing interval of post notches = 2" on center.

A. Spacing Interval as illustrated = 22".

A1. Shelf Clearance as illustrated is 20 3/4", always 1 1/4" less than A.

B. Outside Shelf Length is 1/8" less than nominal.  
(Example: 48" long shelf measures 47 7/8".)

B1. Length Clearance Between Posts is always 2 7/8" less than nominal.  
(Example: 48" long shelf clearance measures 45 1/8".)

C. Outside Shelf Width is always 1/8" more than nominal.  
(Example: 18" width shelf measures 18 1/8".)

C1. Width Clearance Between Posts is always 2 11/16 less than nominal.  
(Example: 18" width shelf clearance measures 15 5/16".)

Z. Minimum Clearance from bottom post notch to the floor is 1 1/4".

#### Mobile Unit Dimensions

Add 3" width and 3" length to nominal shelf size of mobile units to allow for the added dimensions of casters and bumpers. For the overall height of mobile units, add the diameter of the caster to the height of the post plus 1". For example, a 5" diameter caster used with a 64" high post will provide an overall unit height of 70".

### 4-SELF STATIONARY SECURITY UNITS

Dimensions		Weight		Plating Plus™	Polygard® (Blue)
IN W x L x H	MM W x L x H	LBS.	KG.	Cat. No.	Cat. No.
18 X 30 X 72	455 X 760 X 1830	129	58.6	SU1297CP	SU1297PG
24 X 30 X 72	610 X 760 X 1830	143	65	SU1313CP	SU1313PG
18 X 36 X 72	455 X 914 X 1830	135	61.2	SU1298CP	SU1298PG
24 X 36 X 72	610 X 914 X 1830	149	67.5	SU1314CP	SU1314PG
18 X 48 X 72	455 X 1220 X 1830	205	93.1	SU1300CP	SU1300PG
24 X 48 X 72	610 X 1220 X 1830	213	96.8	SU1316CP	SU1316PG
18 X 60 X 72	455 X 1525 X 1830	213	96.8	SU1302CP	SU1302PG
24 X 60 X 72	610 X 1525 X 1830	237	107.7	SU1318CP	SU1318PG

### 4-SHELF MOBILE SECURITY UNITS

Dimensions		Weight		Plating Plus™	Polygard® (Blue)
IN W x L x H	MM W x L x H	LBS.	KG.	Cat. No.	Cat. No.
18 X 30 X 69	455 X 760 X 1753	127	57.5	SU1169CPMO	SU1297PGMO
24 X 30 X 69	610 X 760 X 1753	141	63.9	SU1185CPMO	SU1313PGMO
18 X 36 X 69	455 X 914 X 1753	133	60.2	SU170CPMO	SU1298PGMO
24 X 36 X 69	610 X 914 X 1753	147	66.6	SU1154CPMO	SU1314PGMO
18 X 48 X 69	455 X 1220 X 1753	203	92.0	SU1172CPMO	SU1300PGMO
24 X 48 X 69	610 X 1220 X 1753	211	95.6	SU1188CPMO	SU1316PGMO
18 X 60 X 69	455 X 1525 X 1753	211	95.6	SU1174CPMO	SU1302PGMO
24 X 60 X 69	610 X 1525 X 1753	235	106.5	SU1190CPMO	SU1318PGMO

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke

SPG International, LLC  
11230 Harland Drive NE  
Covington, GA 30014  
877-503-4SPG (4774)

www.spgusa.com

The best names in the business  
all have one thing in common.

EXPECT MORE

**SPG**  
STORAGE PRODUCTS GROUP